

Europäisches Patentamt European Patent Office Office européen des brevets



(11) EP 1 136 050 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:

26.09.2001 Bulletin 2001/39

(51) Int Cl.7: **A61F 13/15**, D04H 11/00, B26F 1/26, A61F 13/02

(21) Application number: 00115481.4

(22) Date of filing: 18.07.2000

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE Designated Extension States: AL LT LV MK RO SI

(30) Priority: 22.03.2000 US 532239

(71) Applicant: McNEIL-PPC, INC. Skillman, New Jersey 08558 (US)

(72) Inventors:Dabi, ShmuelHighland Park, NJ 08094 (US)

Lasko, Vincent P.
 New Egypt, NJ 08533 (US)

Pilate, Rita R.
 Washington Crossing, PA 18977 (US)

(74) Representative:
Groening, Hans Wilhelm, Dipl.-Ing.
BOEHMERT & BOEHMERT
Franz-Joseph-Strasse 38
80801 München (DE)

(54) Microporous films comprising flocked fibers

(57) This invention relates to microporous films comprising flocked fibers. Such microporous films may

be used as breathable materials in for example absorbent articles, wound care bandages, and skin care patches

Description

[0001] The present invention relates to microporous films comprising flocked fibers, which provide a desirable, breathable material that may be used for example in absorbent articles, wound care products, and skin care products.

1

Background of the Invention

[0002] "Breathable" materials are those that allow gases but not liquids to pass through them. They have found advantageous application as breathable backsheets for products like absorbent articles, such as sanitary napkins and pantitiners. They are also employed in wound care products such as bandages that provide protection from dirt, germs, and water while maintaining an ideal environment for would bealing.

[0003] Common breathable materials include polyurethane films, microporous firms, and laminates of permeable films and nonwovens. Conventional microporous films are made by subjecting a film to ionizing radiation or by leaching out of soluble inclusions on the film using aqueous or non-iqueous solvents. Alternatively, microporous films are made by incorporating micronisize particles into an extruded firm followed by controlled stretching of the film to create small voids in it. See for example, U.S. Patent Nos. 4,923,650 and 5,126,391. However microporous films by themselves are generally not soft feeling and do not mimic the texture of fabric very well. On the other hand, they have excellent resistance to strike through by Irquids.

[0004] A variety of film nonwoven laminates are also known to provide breathability. Such laminates advantageously have the attributes of a fabric for example. U.S. Patent No. 5.932,497 discloses a breathable film loaded with a filler and stretched in at least two directions laminated to a nonwoven web.

[0005] Flocking is a technique by which floers are fixed in a vertical position on a substrate, and is primarily used in the fabric industry. However, EP 0.737,462,A1 discloses a laminated material to cover the outside of an absorbent product such as a sanitary hapkin, characterized in that at least one portion of the surface of the laminated material bears a layer of fibors applied by flocking. The flocked fibers are thereby located on the external surface of the absorbent product in order to give the absorbent product improved tactile properties over products that employ plastic films against the skin.

[0006] It has now been discovered that a microporous film comprising flocked fibers may be made. Such a composite material provides good breathability with low liquid strike through. It may be used in absorbent articles, in particular as a backsheet on sanitary protection articles. It may also be used as a component of a wound care bandage or skin care patch. Surprisingly, the application of flocked fibers to a microporous film does not impair its overall breathability. At the same time, the mi-

croporous film is endowed with a soft surface. The flocking also provides a vehicle for holding additives like moisturizers, medicaments, and the like on the microporous film.

Summary of the Invention

[0007] The invention provides a microporous film comprising flocked fibers, as well as an absorbent article, wound care bandage, or skin care patch comprising such a microporous film.

Brief Description of the Drawings

[0008] Figure 1 depicts a pantiliner comprising a backsheet made from a microporous film comprising flocked fibers.

Detailed Description of the Invention

[0009] The microporous film may be of any type. The nature of the microporous film is not critical to the invention. Examples of microporous films include the EXAIRE XBF scries of microporous films commercially available from Tredegar Industries, Inc. and 3M Microporous Film and 3M Face Fresh'ner Film both commercially available from 3M.

[0010] The flocked fibers may be hydrophilic, hydrophobic, or a combination of the two. Hydrophilic fibers include wettable fibers, i.e., hydrophobic fibers that have been treated with a wetting agent to render them hydrophilic, absorbent fibers, and superabsorbent polymer fibers. Examples of wettable fibers include bicomponent fibers, polypropylene fibers, and polyester fibers that have been treated for example with surfactants. Preferred wettable fibers are polyester fibers, such as DuPont-Akra Polyester Type 11A Bright commercially available from DuPont Company treated with a surfactant such as Tween 20 commercially available from ICI Americas Inc.

[0011] Absorbent fibers are hydrophilic fibers that both that have an affinity for and absorb fluids. Absorbent fibers may comprise rayon fibers, acrylic fibers, nylon fibers, polyvinyl alcohol fibers, and fibers of natural or regenerated cellulosics. A preferred type of absorbent fiber is rayon fibers.

[0012] Superabsorbent polymer fibers are hydrophilic fibers that are swellable and capable of absorbing greater than about 5 grams per gram (of fiber weight) of 1% saline solution. Examples of superabsorbent polymer fibers are polyacrylate fibers, fibers of grafted cellulose, and fibers of malcic acid. Preferred types of superabsorbent polymer fibers include OASIS Type 101, commercially available from Technical Absorbents Limited and CAMELOT, commercially available from Camelot, Alberta. Canada.

[0013] Hydrophobic fibers include certain olefin fibers and large denier polyester fibers, preferably having a

denier of at least 3, more preferably at least 6. A preferred hydrophobic fiber is 15 denier polyester commercially available from DuPont Company.

[0014] Regardless of type, the length of the flocked fibers should be less than about 1 mm, preferably less than about 0.8 mm. The denier of the flocked fibers should be in the range of about 1.2d to about 15d, preferably about 1.8d to about 6d.

[0015] In a particularly preferred embodiment of the invention, the flocked fibers comprise cotton or rayon, preferably having a denier of 3 or less. A microporous film bearing such fibers is particularly suitable for use in absorbent articles, especially sanitary protection articles, for example as a breathable backsheet.

[0016] The fibers are applied to one or more surfaces of the microporous film by the process of flocking. Methods of flocking fibers onto a surface are known in the art of fabric manufacture. See for example, U.S. Patent Nos. 2,527,501; 2,691,611; 3,436,442; and 3,672,929. Typically, the microporous film is coated with adhesive on all or a portion of its surface. The coated microporous film is then passed through a fiber metering station, in which an electrostatic field is maintained around it, using for example electrodes situated above and below the microporous film. The fibers are applied to the adhesive on the microporous film in the presence of the electrostatic field, which orients the fibers perpendicular to the microporous film as they contact the adhesive. The microporous film is then heated, polymerizing the adhesive and anchoring the fibers. Care should be taken not to crosslink or cure the adhesive. Unattached fibers may be vacuumed away.

[0017] Preferably, the adhesive employed to attach the fibers to the microporous film is a polymerizable resin. such as modified acrylic water based compounds, for example FLEXBOND 974, 977, 983, and 986 commercially available from Air Products, CARBOTAC Adhesives (PSAs) commercially available from BF Goodrich, and CARBOBOND Adhesives (non-PSAs) also commercially available from BF Goodrich.

[0018] The flocked fibers may be adhered to all or a portion of the microporous film. The flocked fibers may be on one or both sides of the microporous film. The same or different flocked fibers may be on two or more different areas or sides of the microporous film. Mixtures of different types of flocked fibers may also be employed. Depending on the intended use of the microporous film, the nature and amount of flocked fibers thereon can be tailored accordingly.

[0019] The microporous film may comprise one or more additives such as odor control agents, perfumes, medicaments, moisturizing compositions, and the like, many examples of which are known in the art. The additive may be dispersed within the flocked fibers, which act as a vehicle for holding the additive.

[0020] The microporous film comprising flocked fibers is particularly useful as a breathable backsheet for an absorbent article. The absorbent article may for exam-

ple be a sanitary protection product, such as a sanitary napkin, pantiliner, diaper, incontinence pad, interlabial article, or other similar product for absorbing exudates from the body, such as menses, urine, or feces. Such sanitary napkin or pantiliner may have an approximately rectangular, oval, dogbone, or peanut shape. Depending on the nature of the absorbent article, its size may vary. For example, sanitary napkins typically have a caliper of about 1.4 to about 5 mm, a length of about 3 to about 16 inches, and a width of about 1 to about 5 inches. Pantiliners typically have a caliper of less than about 0.2 inches, a length of less than about 8 inches, and a width of less than about 3 inches.

[0021] Figure 1 depicts a pantiliner comprising a backsheet made from a microporous film comprising flocked fibers, and is used for purposes of illustration in the following description. The pantiliner shown in Figure 1 comprises in sequence from its body-facing surface 1 to its garment-facing surface 2 liquid permeable cover 3, an absorbent core 4, and a backsheet 5 comprising the microporous film. The cover 3 of the absorbent article may be formed from any fluid pervious material that is comfortable against the skin and permits fluid to penetrate to the absorbent core, which retains the fluid. The cover should retain little or no fluid to provide a relatively dry surface, since its external surface forms the bodyfacing surface 1 of the article. A variety of materials are known for preparing covers, and any of these may be used. For instance, the cover may be a fibrous non-woven fabric made of natural or polymeric fibers or filaments such as polyethylene, polypropylene, polyester, or cellulose. Alternatively, the cover may be formed from an apertured polymeric film. The thickness of the cover may vary from approximately 0.001 to 0.062 inch, depending on the material chosen.

4

[0022] Generally, cover 3 is a single sheet of material having a width sufficient to form the body-facing surface 1 of the article. The cover may be the same length, or optionally longer than the absorbent core so as to form transverse ends. Such transverse ends may be sealed with other layers to fully enclose the absorbent core.

[0023] The absorbent core 4 may be comprised of a loosely associated absorbent hydrophilic material such as cellulose fibers, including wood pulp, regenerated cellulose fibers or cotton fibers, or other absorbent materials generally known in the art, including acrylic fibers, polyvinyl alcohol fibers, peat moss and superabsorbent polymers.

[0024] The exterior of backsheet 5 forms the garmentfacing surface 2 of the article. When the microporous film comprising flocked fibers is used as a breathable backsheet, the flocked fibers are preferably present on the surface of the microporous film that forms the garment-facing surface 2 of the article.

[0025] Generally, the width of the backsheet 5 is sufficient to form the garment-facing surface 2 of the absorbent article. The backsheet may extend around the sides of the absorbent core in a C-shaped configuration.

35

with the portions of the backsheet adjacent its longitudinal edges extending upwardly from the garment-facing surface toward the body-facing surface of the article. [0026] The absorbent article may be applied to the crotch of underpants by placing the garment-facing surface 2 of the absorbent article against the inside surface of the crotch of the underpants. Strips of pressure sensitive adhesive 6 may be applied to the garment-facing surface 2 of the absorbent article to help maintain it in place. As used herein, the term "pressure-sensitive adhesive" refers to any releasable adhesive or releasable tenacious means. Suitable pressure sensitive adhesives include for example water-based adhesives such as acrylate adhesives. Alternatively, the adhesive may comprise rapid setting thermoplastic "hot melt" rubber adhesives or two-sided adhesive tape.

[0027] A paper release strip 7 that has been coated on one side may be applied to protect the strips of adhesive 6 prior to use. The coating, for example silicone, reduces adherence of the coated side of the release strip to the adhesive. The release strip can be formed from any suitable sheet-like material which, when coated, adheres with sufficient tenacity to the adhesive to remain in place prior to use but can be readily removed when the absorbent article is to be used.

[0028] The absorbent article may comprise other known materials. layers, and additives, such as transfer layers, foam layers, net-like layers, and the like. The absorbent article can optionally be embossed with decorative designs using conventional techniques.

[0029] The microporous film comprising flocked fibers may also be used, for example, as a component of a wound care bandage. In such a wound care bandage, the microporous film may be used as a backing material, which can for example be coated with a pressure sensitive adhesive and attached to an absorbent pad. The flocked fibers can be either on the outer surface of the bandage, providing low friction and low self adhesion for removal and aesthetics, or on the inside surface of the bandage, facing the skin for softness and absorbency. The wound care bandage may further comprise other optional components known in the art.

[0030] The microporous film comprising flocked fibers may also be used as a skin care patch, preferably disposable, for delivering moisturizing compositions, medicaments, perfumes, odor control agents, and the like to the skin. For example, a skin care patch may comprise a microporous film with flocked fibers on one side. Dispersed within the flocked fibers is a moisturizing composition, for example comprising glycerin.

[0031] In another embodiment of the invention, such a skin care patch may comprise one or more medicaments or natural ingredients dispersed within the flocked fibers. Examples of medicaments include salicylic acid, retinol, and benzoyl peroxide. Examples of natural ingredients include soy milk, menthol, and vitamins A, C and E. Adhesive may be applied over the medicament-containing flocked fibers, preferably in a discontinuous pattern, so that the skin care patch may be temporarily attached to the skin.

[0032] The following example further illustrates the invention, but us not intended to limit the claimed invention.

Example 1

[0033] A microporous film according to the invention comprising flocked fibers of cotton is made as follows. EXAIRE TDO-XBF-116W, a 35 gsm microporous film commercially available from Tredegar is employed. A polymerizable resin is applied to the microporous film by rotary screen printing. Cotton fibers having a denier of less than 3 are metered onto the microporous film. The fibers are oriented in the vertical position via an electrostatic field. The fibers adhere where the resin has been applied. The film is then passed through an oven to polymerize the resin, anchoring the fibers to the film. The excess fibers are vacuumed away.

[0034] The microporous film may be used a breathable backsheet in a pantiliner.

Example 2

25

[0035] A non-occlusive skin care patch for the delivery of an acne-treating medicament is made according to the invention as follows. 3M Microporous Film is coated with flocked fibers in the same manner as Example 1 to form a 5 mil layer of flocking on one surface. A water solution containing 20% by weight of polyvinyl pyrrolidone (Kollidon 90 commercially available from BASF), 3% glycerin and 2% salicylic acid is applied to the fiberbearing side of the film and irradiated with a 2.5 Mrad energy electron beam to crosslink the polyvinyl pyrrolidone and form a stable, sticky gel. The final laminate is cut into various sizes for applying to skin for acne treatment.

Example 3 40

45

[0036] A disposable wound care bandage according to the invention is made as follows. 3M Microporous Film is coated with hydrophobic flocked fibers comprising polypropylene and polyester on one side in the manner described in Example 1. The non-flocked side of the film is spray coated with HL 1417, a pressure sensitive, hot melt adhesive commercially available from H.B. Fuller. An absorbent pad is made by laminating a needle punched 90/10 polypropylene/rayon fabric having a ba-50 sis weight of 60 gsm with a Delnet apertured film, commercially available from the AET company.

[0037] A 70X20 mm strip of the flocked, microporous film is cut. A 20x20 mm square of the absorbent pad is cut and glued via its fabric side to the adhesive side of the flocked film to form the wound are bandage.

10

20

25


Claims

- 1. A microporous film comprising flocked fibers.
- The microporous film of claim 1, wherein the flocked fibers are selected from the group consisting of hydrophilic fibers, hydrophobic fibers, and mixtures thereof.
- The microporous film of claim 2, wherein the hydrophilic fibers are selected from the group consisting of wettable fibers, absorbent fibers, superabsorbent polymer fibers, and mixtures thereof.
- The microporous film of claim 1, wherein the flocked fibers are selected from the group consisting of cotton, rayon, and mixtures thereof.
- The microporous film of claim 1 further comprising an additive selected from the group consisting of moisturizing compositions, medicaments, perfumes, odor control agents, and mixtures thereof.
- **6.** An absorbent article comprising a microporous film comprising flocked fibers.
- The absorbent article of claim 5, wherein the microporous film is a backsheet for the absorbent article.
- 8. The absorbent article of claim 5, wherein the microporous film comprises flocked fibers selected from the group consisting of hydrophilic fibers, hydrophobic fibers, and mixtures thereof.
- The absorbent article of claim 7, wherein the hydrophilic fibers are selected from the group consisting of wettable fibers, absorbent fibers, superabsorbent polymer fibers, and mixtures thereof.
- The absorbent article of claim 7, wherein the flocked fibers are selected from the group consisting of cotton, rayon, and mixtures thereof.
- A sanitary napkin comprising a microporous film comprising flocked fibers.
- A pantiliner comprising a microporous film comprising flocked fibers.
- 13. A wound care bandage comprising a microporous film comprising flocked fibers.
- A skin care patch comprising a microporous film comprising flocked fibers.
- 15. The skin care patch of claim 14 further comprising a moisturizing composition dispersed within the flocked fibers.

- **16.** The skin care patch of claim 15, wherein the moisturizing composition comprises glycerin.
- The skin care patch of claim 14 further comprising a medicament dispersed within the flocked fibers.
- The skin care patch of claim 17 wherein the medicament comprises salicylic acid.

5

55





EUROPEAN SEARCH REPORT

Application Number

EP 00 11 5481

| Category | Citation of document with indic of relevant passage | | Relevant to claim | CLASSIFICATION OF THE APPLICATION (Int.CI.7) | |
|---------------------------------------|---|---|---|---|--|
| X Y | US 4 308 303 A (MASTR AL) 29 December 1981 * column 1, line 40 - * column 4, line 37 - * column 7, line 15 - | (1981-12-29) line 48 * line 46 * | 1-4 6-12 | A61F13/15 D04H11/00 B26F1/26 A61F13/02 | |
| Y | EP 0 737 462 A (PANTE 16 October 1996 (1996 * column 3. line 7 - * column 5. line 5 - * column 6, line 32 - * claims; figures * | -10-16) column 4. line 16 * line 54 * | 6-12 | | |
| X | US 6 028 017 A (RUSSEI 22 February 2000 (2000 * column 6, line 44 - * column 7, line 51 - | 3-02-22) line 64 * | 1-3 | | |
| X | GB 1 196 071 A (FARBER AKTIENGESELLSCHAFT) 24 June 1970 (1970-06- * page 1. line 58 - 1- * page 2. line 101 - | -24) ine 61 * | 1-5 | TECHNICAL FIELDS SEARCHED (Int.CI.7) | |
| x | GB 2 077 142 A (TORAY 16 December 1981 (1983 * page 2, line 111 - 1 * page 3, line 20 - 1 | l-12-16) ine 115 * | 1 | D04H B26F | |
| A | US 5 643 237 A (BOULAN 1 July 1997 (1997-07-0 * column 2, line 14 - * column 3, line 17 - * claim 1 * | 11) line 36 * | 1-18 | | |
| | The present search report has been | | | | |
| | THE HAGUE | Date of completion of the search 20 March 2001 | Bara | athe, R | |
| X parti Y parti docu A techi | ATEGORY OF CITED DOCUMENTS cutarly relevant if taken alone cutarly relevant if combined with another ment of the same category sological background written desclosure | T : theory or princip E : earther patent do after the fiting da D : document cited L : document cited | In underlying the scument, but publis te in the application or other reasons | nvention shed on, or | |



EUROPEAN SEARCH REPORT

Application Number EP 00 11 5481

| | DOCUMENTS CONSIDERS Citation of document with indica | | Relevant | CLASSIFICATION OF THE |
|---------|--|--|---|---|
| ategory | Citation of document with indica of relevant passages |) | to claim | APPLICATION (Int.CI.7) |
| A | US 4 324 246 A (MULLAN 13 April 1982 (1982-04 * column 4. line 38 - * column 7. line 19 - * column 9, line 25 - | 1-13) column 9, line 9 * line 38 * | 1-18 | |
| A | US 3 967 623 A (ELIAS 6 July 1976 (1976-07-0 * column 2, line 17 - | 16) | 1-18 | |
| А | EP 0 861 646 A (UNI CI 2 September 1998 (1991 * column 4, line 49 - | 8-09-02) | 1-18 | |
| | | | | TECHNICAL FIELDS SEARCHED (Int.C1.7) |
| | | | | |
| | The present search report has be | een drawr up for all claims | | |
| | Place of search | Date of completion of the sear | ľ | Example |
| | THE HAGUE | 20 March 2001 | В | arathe, R |
| A. | CATEGORY OF CITED DOCUMENTS particularly relevant if taken alone particularly relevant if combined with anoth document of the same category technological background non-written discosure intermediate document | E : eartier pale after the fil eff D : document L : document | cited in the applical cited for other reas- of the same patent to | tion |

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 00 11 5481

This arrows are the payer transferment with a second transferment of the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way habite for these particulars which are merely given for the purpose of information.

20-03-2001

| Fran Lifed | au restou lebo | :: | Hut-scason date | | Patent family member(s) | Publication date |
|---------------|----------------|----|--------------------|-----|----------------------------|---------------------|
| US 4 | 308303 | A | 29-12-1981 | NON | E | |
| EP C | 737462 | A | 16-10-1996 | AT | 196416 T | 15-10-200 |
| | | | | DE | 69518906 D | 26-10-200 |
| | | | | DE | 69518906 T | 01-03-200 |
| | | | | ES | 2149947 T | 16-11-200 |
| | | | | PT | 737462 T | 31-01-200 |
| US 6 | 028017 | A | 22-02-2000 | NON | E | |
| GB 1 | 196071 | A | 24-06 1970 | BE | 708987 A | 16-05-196 |
| | | | | DE | 1729868 A | 24-02-197 |
| | | | | FR | 1550024 A | 13-12-196 |
| | | | | NL | 6800022 A | 08-07-196 |
| GB 2 | C77:42 | A | 16-12-1981 | JP | 56159368 A | 08-12-198 |
| | | | | DE | 3117894 A | 11-03-198 |
| | | | | FR. | 2482144 A | 13-11-198 |
| us s | 643237 | A | 01-07-1997 | AU | 593653 B | 15-02-199 |
| | | | | AU | 7366287 A | 03-12-198 |
| | | | | BR | 8702778 A | 01-03-198 |
| | | | | CA | 1263064 A | 21-11-198 |
| | | | | DE | 3783677 A | 04-03-199 |
| | | | | DE | 3783677 T | 27-05-199 |
| | | | | DK | 278187 A | 01-12-198 |
| | | | | £P | 0255209 A | 03-02-198 |
| | | | | ES | 2039438 T | 01-10-199 |
| | | | | FI | 872402 A | 01-12-198 |
| | | | | HIX | 99493 A | 30-09-199 |
| | | | | IE | 60372 B | 13-07-199 |
| | | | | IN | 168576 A | 04-05-199 |
| | | | | JP | 2543365 B | 16-10-199 |
| | | | | JP | 63051857 A | 04-03-198 |
| | | | | K R | 9408079 B | 01-09-199 |
| | | | | MI | 169496 B | 08-07-199 |
| | | | | NC | 872264 A | 01-12-198 |
| | | | | NZ | 220354 A | 29-01-199 |
| | | | | PH | 27212 A | 04-05-199 |
| | | | | ZA | 8703897 A | 25-01-198 |
| US 4 | 324246 | Α | 13-04-1982 | AT | 9058 T | 15-09-198 |
| | | | | AU | 538763 B | 23-08-198 |
| | | | | AU | 7044381 A | 26-11-198 |
| | | | | BR | 8102868 A | 02-02-198 |
| | | | | CA | 1150905 A | 02-08-198 |

E. For more details about this annex usee Official Journal of the European Patent Office, No. 12/82.

EP 1 136 050 A1

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 00 11 5481

This annex itsis the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP tile on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

20-03-2001

| Patent document | | Publication date | F | Patent family member(s) | Publication date |
|-----------------|---|------------------|--|---|--|
| us 4324246 | A | | DE EP ES FI FR GR HK IE JP JP MX PH | 3165647 D 0039974 A 258204 U 811450 A.B. 1573207 A 73079 A 61785 A 51247 B 4022578 B 57001340 A 155645 A 17235 A | 27-09-1984 18-11-1981 01-04-1982 13-11-1981 04-07-1969 31-01-1984 23-08-1985 12-11-1986 17-04-1992 06-01-1982 11-04-1988 03-07-1984 |
| us 3967623 | Α | 06-07-1976 | NON | E | |
| EP 0861646 | Α | 02-09-1998 | JP CN SG | 10234776 A 1203068 A 71085 A | 08-09-1998 30-12-1998 21-03-200 |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| 1 | | | | | |

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82